PHYTO EXPLO@ FUMIGATION APPLIED IN SILOS

B. VACQUER¹, G. ZAKLADNOy², A. VASILIEV², E. BELOBROV³, J. ROGERSON⁴, B. KUGLER⁵ and M. ABDULLAEV⁶

 ¹ DM France, 34 Rue du Contrat Social, Rouen, 76000, France
² Research Institute for Grain and Processed Grain Products (VNIIZ), 11 Dmitrovskoye Chaussee, Moscow 127434, Russia
³ Research Institute for Navigation Transport Hygiene (VNIIGIVT), 22 Voljski Street, Odessa 270046, Ukraine
⁴ Igrox Chemicals Ltd., White Hall Farm, Worlingworth, Woodbridge, Suffolk IP13 7HW, United Kingdom
⁵ D.M.I.G., 67 me de la ServeUe, 1202 Geneva, Switzerland
⁶ Stored Grain Pest Protection Service, 36 Lakhuty, Tashkent, Uzbekistan

ABSTRACT

The use of PHYTO EXPLO@ equipment for the application of phosphine or methyl bromide in silo bins is described. For phosphine fumigation, aluminium phosphide packages manufactured specifically for the purpose are inserted into the PHYTO SHAFT@ tube, whereas methyl bromide is applied directly to the grain mass and its distribution is achieved using a fan connected to the PHYTO SHAFT@ tube for recirculation. The same fan can be reversed for degassing of the bin after fumigation. Trials to determine the time needed for penetration of the PHYTO EXPLO@ shaft into the grain mass revealed that between 52 and 79 min were needed to reach a depth of 20 m in a bulk of wheat. The withdrawal of the equipment from the grain mass took from 77 to 85 min.